



HD LOW PROFILE DUAL RAM DUMP

	82" x 12, 12K	82" x 12, 14K	82" x 14, 14K
Model #	ST8212DD-B-120	ST8212DD-B-140	ST8214DD-B-140
GVWR (lbs)	12000	14000	14000
GAWR (lbs/axle)	6000	7000	7000
Curb Weight	3500	3720	3880
Payload	8500	10280	10120
Frame	5 x 2, 3/16" Tube	6 x 2, 3/16" Tube	6 x 2, 3/16" Tube
Cross Members	4" C-Channel		
Tongue	5 x 2 Tube	6 x 2 Tube	6 x 2 Tube
Sides	24"		
Coupler	Adjustable 2-5/16" Ball Coupler		
Jack	Setback 7K Drop Leg Jack	Setback HD 12K Drop Leg Jack	
Fenders	Heavy Duty Tread Plate, Double Brake		
Easy Lube Axles	Easy Lube Cambered Brake		
Suspension	Slipper Spring		
Tires	235/80R16 LRE		
Wheels	16", 8 on 6.5, Radial		
Decking	10 Ga. Smooth Steel		
Lights	All LED Lights		
Electric Plug	7-Way RV-Style Molded Plug		
Finish	Powder Coated High Gloss Black		
Overall Length	198"	198	222"
Bed Length Inside	144"	144	168"
Bed Width Inside	82"	82	82"
Bed Height Inside	24	24	24"
Deck Height	29"	29	29"
Coupler Height	Adjustable 19-27"		
Gate	Combination Barn Door Spreader Gate with Cambar		
Hydraulic Hoist	Power Up, Power Down		
Pump	2300 PSI	3000 PSI	3000 PSI
Battery	Group 24 Deep Cycle	Group 24 Deep Cycle	Group 24 Deep Cycle

HD LOW PROFILE DUAL RAM DUMP FEATURES

<ul style="list-style-type: none"> Tube Main Frame 24" Sides Integrated Side Body Stiffening System Board Holders Adjustable 2-5/16" Coupler Safety Chains 7-Way RV-Style Molded Plug Breakaway Switch with Battery EverLink™ Wiring Harness Sealed Brake Connections Setback 7K Drop Leg Jack (12K Models) Setback HD 12K Drop Leg Jack (14K Models) 	<ul style="list-style-type: none"> Stabilizer Jack Receivers (Jacks Optional) Ramps (Stored Underneath Bed) HD Reinforced Combo Barn Door Spreader Gate w/Cambar Tread Plate Fenders HD Slipper Spring Axles Brakes on Both Axles 16" Radial Tires Silver Wheels Wheel Assembly, 235 80R16 LRE Powder Coat Finish 10-Gauge Floor (5) 1/2" D-rings 	<ul style="list-style-type: none"> Stake Pockets Spare Tire Carrier Side Steps Integrated Tarp Mount Mesh Tarp Kit (Installed) Anti-Sail Kit with Integrated Tie-Down Tongue Mounted HD Control Box with Key Lock Underbody Secure Tool Storage All LED Lights Deep Cycle Battery Battery Charger, 110-Volt Power-Up, Power-Down Hydraulics
---	---	---



Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



HD LOW PROFILE TELESCOPIC DUMP

	82" x 12, 12K	82" x 12, 14K	82" x 14, 14K	82" x 16, 14K	82" x 14, 16K	82" x 16, 16K
Model #	ST8212TLDD-B-120	ST8212TLDD-B-140	ST8214TLDD-B-140	ST8216TLDD-B-140	ST8214TLDD-B-160	ST8216TLDD-B-160
GVWR (lbs)	12000	14000	14000	14000	16000	16000
GAWR (lbs/axle)	6000	7000	7000	7000	8000	8000
Curb Weight	3500	3720	3880	4100	4120	4340
Payload	8500	10280	10120	9900	11880	11660
Frame	6x2, 3/16" Tube	6 x 2, 3/16" Tube	6 x 2, 3/16" Tube	6 x 2, 1/4" Tube		
Cross Members	4" C-Channel					
Tongue	6 x 2 Tube	6 x 2 Tube	6 x 2 Tube	6 x 2 Tube	8 x 2 Tube	8 x 2 Tube
Sides	24"					
Coupler	Adjustable 2-5/16" Ball Coupler			Adjustable 4-Bolt Pintle Eye		
Jack	Setback 7K Drop Leg Jack	Setback HD 12K Drop Leg Jack				
Fenders	Heavy Duty Tread Plate, Double Brake					
Easy Lube Axles	Easy Lube Cambered Brake					
Suspension	Slipper Spring					
Tires	235/80R16 LRE			215/75R17.5 LRH		
Wheels	16", 8 on 6.5, Radial			17.5", 8 on 6.5, Radial		
Decking	10 Ga. Smooth Steel					
Lights	All LED Lights					
Electric Plug	7-Way RV-Style Molded Plug					
Finish	Powder Coated High Gloss Black					
Overall Length	198"	198"	222"	246"	222"	246"
Bed Length Inside	144"	144"	168"	192"	168"	192"
Bed Width Inside	82"	82"	82"	82"	82"	82"
Bed Height Inside	24"	24"	24"	24"	24"	24"
Deck Height	29"	29"	29"	29"	29"	29"
Coupler Height	Adjustable 19-27"					
Gate	Combination Barn Door Spreader Gate with Cambar					
Hydraulic Hoist	Telescopic Hoist, Power Up, Gravity Down					
Pump	2300 PSI	2300 PSI	2300 PSI	2300 PSI	2500 PSI	2500 PSI
Battery	Group 24 Deep Cycle	Group 24 Deep Cycle	Group 24 Deep Cycle	Group 24 Deep Cycle	Group 24 Deep Cycle	Group 24 Deep Cycle

16K Models Include

Adjustable 4-Bolt Pintle Eye Coupler, Setback HD 12K Drop Leg Jack, 8" Tongue, 6" Cylinder and Thicker Wall Tube Frame.

HD LOW PROFILE TELESCOPIC DUMP FEATURES

<ul style="list-style-type: none"> Tube Main Frame 24" Sides Integrated Side Body Stiffening System Board Holders Adjustable 2-5/16" Coupler (12K and 14K Models) Adjustable 4-Bolt Pintle Eye Coupler (16K Models) Safety Chains 7-Way RV-Style Molded Plug Breakaway Switch with Battery EverLink™ Wiring Harness Sealed Brake Connections Setback 7K Drop Leg Jack (12K Models) Setback HD 12K Drop Leg Jack (14K and 16K Models) Stabilizer Jack Receivers (Jacks Optional) 	<ul style="list-style-type: none"> Ramps (Stored Underneath Bed) HD Reinforced Combo Barn Door Spreader Gate w/Cambar Tread Plate Fenders HD Slipper Spring Axles 8K Axle(s) with 3-3/8" Brake (16K Models) Brakes on Both Axles Easy Lube Hubs 16" Radial Tires (12K and 14K Models) 17.5" Radial Tires (16K Models) Silver Wheels Wheel Assembly, 235 80R16 LRE (12K and 14K Models) Wheel Assembly, 215 75R17.5 (16K Models) Powder Coat Finish 10-Gauge Floor 	<ul style="list-style-type: none"> (5) 1/2" D-rings Stake Pockets Spare Tire Carrier Side Steps Integrated Tarp Mount Mesh Tarp Kit (Installed) Anti-Sail Kit with Integrated Tie-Down Tongue Mounted HD Control Box with Key Lock Underbody Secure Tool Storage All LED Lights Deep Cycle Battery Battery Charger, 110-Volt Power-Up, Gravity-Down Hydraulics
---	---	---



Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



HD LOW PROFILE SCISSOR DUMP

	82" x 12, 12K	82" x 12, 14K	82" x 14, 14K	82" x 16, 14K	82" x 14, 16K	82" x 16, 16K
Model #	ST8212HLOD-B-120	ST8212HLOD-B-140	ST8214HLOD-B-140	ST8216HLOD-B-140	ST8214HLOD-B-160	ST8216HLOD-B-160
GVWR (lbs)	12000	14000	14000	14000	16000	16000
GAWR (lbs/axle)	6000	7000	7000	7000	8000	8000
Curb Weight	3660	3880	4080	4420	4320	4660
Payload	8340	10120	9920	9580	11680	11340
Frame	5 x 2, 3/16" Tube	6 x 2, 3/16" Tube	6 x 2, 3/16" Tube	6 x 2, 1/4" Tube		
Cross Members	4" C-Channel					
Tongue	5 x 2 Tube	6 x 2 Tube	6 x 2 Tube	6 x 2 Tube	8 x 2 Tube	8 x 2 Tube
Sides	24"					
Coupler	Adjustable 2-5/16" Ball Coupler				Adjustable 4-Bolt Pintle Eye	
Jack	Setback 7K Drop Leg	Setback HD 12K Drop Leg Jack				
Fenders	Heavy Duty Tread Plate, Double Brake					
Easy Lube Axles	Easy Lube Cambered Brake					
Suspension	Slipper Spring					
Tires	235/80R16 LRE				215/75R17.5 LRH	
Wheels	16", 8 on 6.5, Radial				17.5", 8 on 6.5, Radial	
Decking	10 Ga. Smooth Steel					
Lights	All LED Lights					
Electric Plug	7-Way RV-Style Molded Plug					
Finish	Powder Coated High Gloss Black					
Overall Length	198"	198"	222"	246"	222"	246"
Bed Length Inside	144"	144"	168"	192"	168"	192"
Bed Width Inside	82"	82"	82"	82"	82"	82"
Bed Height Inside	24"	24"	24"	24"	24"	24"
Deck Height	29"	29"	29"	29"	29"	29"
Coupler Height	Adjustable 19-27"					
Gate	Combination Barn Door Spreader Gate with Cambar					
Hydraulic Hoist	Power Up, Gravity Down					
Pump	2500 PSI	2800 PSI	2800 PSI	2500 PSI	2800 PSI	2800 PSI
Battery	Group 24 Deep Cycle	Group 24 Deep Cycle	Group 24 Deep Cycle	Group 31 Deep Cycle	Group 24 Deep Cycle	Group 31 Deep Cycle

16K Models Include

Adjustable 4-Bolt Pintle Eye Coupler, Setback HD 12K Drop Leg Jack, 8" Tongue, 6" Cylinder and Thicker Wall Tube Frame.

HD LOW PROFILE SCISSOR DUMP FEATURES

<ul style="list-style-type: none"> Tube Main Frame 24" Sides Integrated Side Body Stiffening System Board Holders Adjustable 2-5/16" Coupler (12K and 14K Models) Adjustable 4-Bolt Pintle Eye Coupler (16K Models) Safety Chains 7-Way RV-Style Molded Plug Breakaway Switch with Battery EverLink™ Wiring Harness Sealed Brake Connections Setback 7K Drop Leg Jack (12K Models) Setback HD 12K Drop Leg Jack (14K and 16K Models) Stabilizer Jack Receivers (Jacks Optional) 	<ul style="list-style-type: none"> Ramps (Stored Underneath Bed) HD Reinforced Combo Barn Door Spreader Gate w/Cambar Tread Plate Fenders HD Slipper Spring Axles 8K Axle(s) with 3-3/8" Brake (16K Models) Brakes on Both Axles Easy Lube Hubs 16" Radial Tires (12K and 14K Models) 17.5" Radial Tires (16K Models) Silver Wheels Wheel Assembly, 235 80R16 LRE (12K and 14K Models) Wheel Assembly, 215 75R17.5 (16K Models) Powder Coat Finish 10-Gauge Floor 	<ul style="list-style-type: none"> (5) 1/2" D-rings Stake Pockets Spare Tire Carrier Side Steps Integrated Tarp Mount Mesh Tarp Kit (Installed) Anti-Sail Kit with Integrated Tie-Down Tongue Mounted HD Control Box with Key Lock Underbody Secure Tool Storage All LED Lights Deep Cycle Battery Battery Charger, 110-Volt Power-Up, Gravity-Down Hydraulics
---	---	---



Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.