



SPECIFICATIONS -STEEL DECKOVER STANDARD DUTY STEEL BP DECKOVER FLATDECK LIGHT DUTY 10K

	102 x 14		102 x 16		102 x 18		102 x 20		102 x 22		102 x 24	
Model #	H-SDOF14-100		H-SDOF16-100		H-SDOF18-100		H-SDOF20-100		H-SDOF22-100		H-SDOF24-100	
CAPACITIES												
GVWR (lbs)	10000											
GAWR (lbs/axle)	5200											
Curb Weight	2770		2530		2810		3150		3450		3650	
Payload	7230		7470		7190		6850		6550		6350	
CHASSIS												
Coupler	2-5/16" Adjustable											
Tongue	6" Steel Channel, Fully Wrapped											
Tongue Jack	7K Drop Leg, Set-Back											
Frame	10", 12 lb/ft I-Beam											
Crossmembers	3" Steel Channel											
Integrated Step(s)	Side Steps											
Axle	(2) 5200 lb. Spring Brake											
Hubs	Easy Lube											
Exterior Finish	Industrial Grade Polymer Finish											
Tires	ST225/75R15D 8-PLY											
Wheels	15", 6-Lug Steel											
Tie Downs	1/4" Steel Rub Rails, Stake Pockets											
Wiring	Sealed Wiring Harness											
Exterior Lights	Full LED, DOT Compliant											
Mud Flaps	Yes											
Decking	2" Pressure Treated Pine											
Exterior Storage	Spare Tire Carrier											
Coupler Height	11-19											
Deck Height	31		30									
Height Overall	38											
Width Interior	97.25											
DIMENSIONS												
Overall Length	228		252		276		300		324		348	
Deck Width	97.25											
Deck Height	31		30									
Coupler Height	11-19											

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -STEEL DECKOVER STANDARD DUTY STEEL BP DECKOVER FLATDECK LIGHT DUTY 14K

	102 x 14	102 x 16	102 x 18	102 x 20	102 x 22	102 x 24
Model #	H-SDOF14-140	H-SDOF16-140	H-SDOF18-140	H-SDOF20-140	H-SDOF22-140	H-SDOF24-140
CAPACITIES						
GVWR (lbs)	14000					
GAWR (lbs/axle)	7000					
Curb Weight	2850	2800	3130	3460	3600	4050
Payload	11150	11200	10870	10540	10400	9950
CHASSIS						
Coupler	2-5/16" Adjustable					
Tongue	6" Steel Channel, Fully Wrapped					
Tongue Jack	12K Drop Leg, Set-Back					
Frame	10", 12 lb/ft I-Beam					
Crossmembers	3" Steel Channel					
Integrated Step(s)	Side Steps					
Axle	(2) 7000 lb. Slipper Spring Brake					
Hubs	Easy Lube					
Exterior Finish	Industrial Grade Polymer Finish					
Tires	ST235/80R16E 10-PLY					
Wheels	16", 8-Lug Steel					
Tie Downs	1/4" Steel Rub Rails, Stake Pockets					
Wiring	Sealed Wiring Harness					
Exterior Lights	Full LED, DOT Compliant					
Bulkhead	Custom Formed					
Mud Flaps	Yes					
Decking	2" Pressure Treated Pine					
Exterior Storage	Spare Tire Carrier					
Coupler Height	11-19					
Deck Height		31				
Height Overall	38					
Width Interior	97.25					
DIMENSIONS						
Overall Length	228	252	276	300	324	348
Deck Width	97.25					
Deck Height		31				
Coupler Height	11-19					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

102 x 28	
Model #	H-SDOF28-140
CAPACITIES	
GVWR (lbs)	14000
GAWR (lbs/axle)	7000
Curb Weight	4120
Payload	9880
CHASSIS	
Coupler	2-5/16" Adjustable
Tongue	6" Steel Channel, Fully Wrapped
Tongue Jack	12K Drop Leg, Set-Back
Frame	10", 12 lb/ft I-Beam
Crossmembers	3" Steel Channel
Integrated Step(s)	Side Steps
Axle	(2) 7000 lb. Slipper Spring Brake
Hubs	Easy Lube
Exterior Finish	Industrial Grade Polymer Finish
Tires	ST235/80R16E 10-PLY
Wheels	16", 8-Lug Steel
Tie Downs	1/4" Steel Rub Rails, Stake Pockets
Wiring	Sealed Wiring Harness
Exterior Lights	Full LED, DOT Compliant
Bulkhead	Custom Formed
Mud Flaps	Yes
Decking	2" Pressure Treated Pine
Exterior Storage	Spare Tire Carrier
Coupler Height	11-19
Height Overall	38
Width Interior	97.25
DIMENSIONS	
Overall Length	396
Deck Width	97.25
Coupler Height	11-19

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -STEEL DECKOVER STANDARD DUTY STEEL GN DECKOVER FLATDECK LIGHT DUTY 14K

	102 x 20	102 x 24
Model #	H-SDOF20-140G	H-SDOF24-140G
CAPACITIES		
GVWR (lbs)	14000	
GAWR (lbs/axle)	7000	
Curb Weight	4300	4500
Payload	9700	9500
CHASSIS		
Coupler	2-5/16" Adjustable Gooseneck	
Tongue	10" Flange, 12 lb/ft I-Beam	
Tongue Jack	Dual 12K Drop Leg	
Frame	10", 12 lb/ft I-Beam	
Crossmembers	3" Steel Channel	
Integrated Step(s)	Side Steps	
Axle	(2) 7000 lb. Slipper Spring Brake	
Hubs	Easy Lube	
Exterior Finish	Industrial Grade Polymer Finish	
Tires	ST235/80R16E 10-PLY	
Wheels	16", 8-Lug Steel	
Tie Downs	1/4" Steel Rub Rails, Stake Pockets	
Wiring	Sealed Wiring Harness	
Exterior Lights	Full LED, DOT Compliant	
Bulkhead	Custom Formed	
Mud Flaps	Yes	
Decking	2" Pressure Treated Pine	
Exterior Storage	Spare Tire Carrier, Recessed In Neck	
Coupler Height	29-37	
Deck Height	31	
Height Overall	38	75
Width Interior	97.25	
Width Ramp		21
Length Ramp		60
DIMENSIONS		
Overall Length	340	388
Deck Width	97.25	
Deck Height	31	
Coupler Height	29-37	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.