



SPECIFICATIONS -STEEL FLATBED - INDUSTRIAL STEEL TOPLINE I-BEAM INDUSTRIAL

8.5 x 22	
Model #	H-BIT8222-176G
CAPACITIES	
GVWR (lbs)	17600
GAWR (lbs/axle)	8000
CHASSIS	
Coupler	Adjustable 4-Bolt Pintle Ring
Tongue	12" Extension, 8" Flange, 13 lb/ft I-Beam
Tongue Jack	12K, 2-Speed Drop Leg
Frame	8", 13 lb/ft I-Beam
Crossmembers	3" Steel Channel
Ramp(s)	24" Wide HD Mesh Covered Stand-Up with Spring Assist
Axle	(2) 8000 lb. Slipper Spring Brake
Hubs	Easy Lube
Exterior Finish	Industrial Grade Polymer Finish
Tires	215/75R17.5J 18-PLY
Wheels	17.5", 8-Lug Steel
Tie Downs	(4) 3/4" D-Rings, Banjo Tie-Downs, Oversize 5" x 1/4" Thick Stake Pockets
Wiring	Sealed Wiring Harness
Exterior Lights	Full LED, DOT Compliant
Bulkhead	HD Bulkhead with Integrated Tie-Down Points
Dovetail	3' Self Cleaning
Decking	2" Pressure Treated Pine, Board Retainers
Exterior Storage	Large Toolbox with Interior Light and Gas Spring, Spare Tire Carrier
Width Ramp	24
Length Ramp	60
DIMENSIONS	
Overall Length	364

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -STEEL FLATBED - INDUSTRIAL STEEL TOPLINE I-BEAM INDUSTRIAL 15.4K

	82 x 18	8.5 x 20	8.5 x 22
Model #	H-BIT8218-154	H-BIT8220-154	H-BIT8222-154
CAPACITIES			
GVWR (lbs)	15400		
GAWR (lbs/axle)	7000		
Curb Weight	3280	3480	3680
Payload	12120	11920	11720
CHASSIS			
Coupler	Adjustable 4-Bolt Pintle Ring		
Tongue	12" Extension, 8" Flange, 13 lb/ft I-Beam		
Tongue Jack	12K, 2-Speed Drop Leg		
Frame	8", 13 lb/ft I-Beam		
Crossmembers	3" Steel Channel		
Ramp(s)	24" Wide HD Mesh Covered Stand-Up with Spring Assist		
Axle	(2) 7000 lb. Slipper Spring Brake		
Hubs	Easy Lube		
Exterior Finish	Industrial Grade Polymer Finish		
Tires	ST235/80R16E 10-PLY		
Wheels	16", 8-Lug Steel		
Tie Downs	(4) 3/4" D-Rings, Banjo Tie-Downs, Oversize 5" x 1/4" Thick Stake Pockets		
Wiring	Sealed Wiring Harness		
Exterior Lights	Full LED, DOT Compliant		
Bulkhead	HD Bulkhead with Integrated Tie-Down Points		
Dovetail	3' Self Cleaning		
Decking	2" Pressure Treated Pine, Board Retainers		
Exterior Storage	Large Toolbox with Interior Light and Gas Spring, Spare Tire Carrier		
Coupler Height	17-26		
Deck Height	22		
Height Overall	35		
Width Between Fender	82.25		
Width Ramp	24		
Length Ramp	60		
DIMENSIONS			
Overall Length	288	312	336
Deck Height	22		
Coupler Height	17-26		

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -STEEL FLATBED - INDUSTRIAL STEEL TOPLINE I-BEAM INDUSTRIAL 17.6K

	82 x 18	8.5 x 20	8.5 x 22
Model #	H-BIT8218-176	H-BIT8220-176	H-BIT8222-176
CAPACITIES			
GVWR (lbs)	17600		
GAWR (lbs/axle)	8000		
Curb Weight	3520	3720	3920
Payload	14080	13880	13680
CHASSIS			
Coupler	Adjustable 4-Bolt Pintle Ring		
Tongue	12" Extension, 8" Flange, 13 lb/ft I-Beam		
Tongue Jack	12K, 2-Speed Drop Leg		
Frame	8", 13 lb/ft I-Beam		
Crossmembers	3" Steel Channel		
Ramp(s)	24" Wide HD Mesh Covered Stand-Up with Spring Assist		
Axle	(2) 8000 lb. Slipper Spring Brake		
Hubs	Easy Lube		
Exterior Finish	Industrial Grade Polymer Finish		
Tires	215/75R17.5J 18-PLY		
Wheels	17.5", 8-Lug Steel		
Tie Downs	(4) 3/4" D-Rings, Banjo Tie-Downs, Oversize 5" x 1/4" Thick Stake Pockets		
Wiring	Sealed Wiring Harness		
Exterior Lights	Full LED, DOT Compliant		
Bulkhead	HD Bulkhead with Integrated Tie-Down Points		
Dovetail	3' Self Cleaning		
Decking	2" Pressure Treated Pine, Board Retainers		
Exterior Storage	Large Toolbox with Interior Light and Gas Spring, Spare Tire Carrier		
Coupler Height	17-26		
Deck Height	22		
Height Overall	35		
Width Between Fender	82.25		
Width Ramp	24		
Length Ramp	60		
DIMENSIONS			
Overall Length	288	312	336
Deck Height	22		
Coupler Height	17-26		

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -STEEL FLATBED - INDUSTRIAL STEEL TOPLINE I-BEAM INDUSTRIAL 22K

	82 x 18	8.5 x 20	8.5 x 22
Model #	H-BIT8218-220	H-BIT8220-220	H-BIT8222-220
CAPACITIES			
GVWR (lbs)	22000		
GAWR (lbs/axle)	10000		
Curb Weight	3920	4120	4320
Payload	18080	17880	17680
CHASSIS			
Coupler	Adjustable 4-Bolt Pintle Ring		
Tongue	12" Extension, 8" Flange, 13 lb/ft I-Beam		
Tongue Jack	12K, 2-Speed Drop Leg		
Frame	8", 13 lb/ft I-Beam		
Crossmembers	3" Steel Channel		
Ramp(s)	24" Wide HD Mesh Covered Stand-Up with Spring Assist		
Axle	(2) 10000 lb. Torsion Brake		
Hubs	Oil Bath		
Exterior Finish	Industrial Grade Polymer Finish		
Tires	215/75R17.5J 18-PLY		
Wheels	17.5", 8-Lug Steel		
Tie Downs	(4) 3/4" D-Rings, Banjo Tie-Downs, Oversize 5" x 1/4" Thick Stake Pockets		
Wiring	Sealed Wiring Harness		
Exterior Lights	Full LED, DOT Compliant		
Bulkhead	HD Bulkhead with Integrated Tie-Down Points		
Dovetail	3' Self Cleaning		
Decking	2" Pressure Treated Pine, Board Retainers		
Exterior Storage	Large Toolbox with Interior Light and Gas Spring, Spare Tire Carrier		
Coupler Height	17-26		
Deck Height	26		
Height Overall	35		
Width Between Fender	82.25		
Width Ramp	24		
Length Ramp	60		
DIMENSIONS			
Overall Length	288	312	336
Deck Height	26		
Coupler Height	17-26		

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.