



SPECIFICATIONS -STEEL GRAVITY TILT STEEL TOPLINE TILT EQUIPMENT 15.4K

	82 x 26	82 x 28	82 x 28	82 x 30
Model #	H-BTE82164-154	H-BTE82184-154	H-BTE82166-154	H-BTE82186-154
CAPACITIES				
GVWR (lbs)	15400			
GAWR (lbs/axle)	7000			
Curb Weight	4040	4070	4140	
Payload	11360	11330	11260	
CHASSIS				
Coupler	Adjustable 4-Bolt Pintle Ring			
Tongue	8" Flange, 13 lb/ft I-Beam			
Tongue Jack	12K, 2-Speed Drop Leg			
Frame	8", 13 lb/ft I-Beam, Tilting Deck - 6" x 4" x 5/16" Reinforced Angle			
Crossmembers	3" x 2" Tube, 16" On-Center			
Axle	(2) 7000 lb. Slipper Spring Brake			
Hubs	Easy Lube			
Exterior Finish	Industrial Grade Polymer Finish			
Tires	ST235/80R16E 10-PLY			
Wheels	16", 8-Lug Steel			
Tie Downs	(4) 3/4" D-Rings, Banjo Tie-Downs, Oversize 5" x 1/4" Thick Stake Pockets			
Wiring	Sealed Wiring Harness			
Exterior Lights	Full LED, DOT Compliant			
Dovetail	Diamond Plate Knife Edge			
Decking	2" Pressure Treated Pine, 4' Stationary, Board Retainers		2" Pressure Treated Pine, 6' Stationary, Board Retainers	
Exterior Storage	Large Toolbox with Interior Light and Gas Spring, Spare Tire Carrier			
Hydraulic Components	Easy Locking Tilt Bed Latch, Hydraulic Cushion Load Cylinder with Stop Valve			
Coupler Height	17-26			
Deck Height	22			
Height Overall	35			
Width Interior	80			
Width Between Fender	82			
Load Angle	14.5			13
Width Tilting Deck	73.75			
DIMENSIONS				
Overall Length	312	336		360
Deck Width	80			
Deck Height	22			
Coupler Height	17-26			

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -STEEL GRAVITY TILT STEEL TOPLINE TILT EQUIPMENT 17.6K

	82 x 26	82 x 28	82 x 28	82 x 30	82 x 30
Model #	H-BTE82164-176	H-BTE82166-176	H-BTE82184-176	H-BTE82186-176	H-BTE82204-176
CAPACITIES					
GVWR (lbs)	17600				
GAWR (lbs/axle)	8000				
Curb Weight	4180	4420		4950	
Payload	13420	13180		12650	
CHASSIS					
Coupler	Adjustable Pintle Ring				
Tongue	8" Flange, 13 lb/ft I-Beam				
Tongue Jack	12K, 2-Speed Drop Leg				
Frame	8", 13 lb/ft I-Beam, Tilting Deck - 6" x 4" x 5/16" Reinforced Angle				
Crossmembers	3" x 2" Tube, 16" On-Center				
Axle	(2) 8000 lb. Slipper Spring Brake				
Hubs	Oil Bath				
Exterior Finish	Industrial Grade Polymer Finish				
Tires	215/75R17.5J 18-PLY				
Wheels	17.5", 8-Lug Steel				
Tie Downs	(4) 3/4" D-Rings, Oversize 5" x 1/4" Thick Stake Pockets				
Wiring	Sealed Wiring Harness				
Exterior Lights	Full LED, DOT Compliant				
Bulkhead	HD Bulkhead with Integrated Tie-Down Points				
Dovetail	Diamond Plate Knife Edge				
Decking	2" Pressure Treated Pine, 4' Stationary, Board Retainers	2" Pressure Treated Pine, 6' Stationary, Board Retainers	2" Pressure Treated Pine, 4' Stationary, Board Retainers	2" Pressure Treated Pine, 6' Stationary, Board Retainers	2" Pressure Treated Pine, 4' Stationary, Board Retainers
Exterior Storage	Large Toolbox with Interior Light and Gas Spring, Spare Tire Carrier				
Hydraulic Components	Easy Locking Tilt Bed Latch, Hydraulic Cushion Load Cylinder with Stop Valve				
Coupler Height	17-26				
Deck Height	22				
Height Overall	35				
Width Interior	80				
Width Between Fender	82				
Load Angle	14.5			13	
Width Tilting Deck	73.75				
DIMENSIONS					
Overall Length	312	336		360	
Deck Width	80				
Deck Height	22				
Coupler Height	17-26				

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -STEEL GRAVITY TILT STEEL TOPLINE TILT EQUIPMENT 22K

	82 x 26	82 x 28	82 x 28	82 x 30
Model #	H-BTE82164-220	H-BTE82184-220	H-BTE82166-220	H-BTE82186-220
CAPACITIES				
GVWR (lbs)	22000			
GAWR (lbs/axle)	8000			
CHASSIS				
Coupler	Adjustable 4-Bolt Pintle Ring			
Tongue	8" Flange, 13 lb/ft I-Beam			
Tongue Jack	12K, 2-Speed Drop Leg			
Frame	8", 15 lb/ft I-Beam			
Crossmembers	3" Steel Channel, 16" On-Center			
Axle	(2) 10000 lb. Torsion Brake			
Hubs	Oil Bath			
Exterior Finish	Industrial Grade Polymer Finish			
Tires	ST235/75R17.15J 18-PLY			
Wheels	17.5", 8-Lug Steel			
Tie Downs	(4) 3/4" D-Rings			
Wiring	Sealed Wiring Harness			
Exterior Lights	Full LED, DOT Compliant			
Bulkhead	HD Bulkhead with Integrated Tie-Down Points			
Dovetail	Diamond Plate Knife Edge			
Decking	2" Pressure Treated Pine			
Exterior Storage	Large Toolbox with Interior Light and Gas Spring			
Coupler Height	17-26			
Deck Height	22			
Height Overall	35			
Width Interior	80			
Width Between Fender	82			
Load Angle	14.5			
Width Tilting Deck	73.75			
DIMENSIONS				
Overall Length	312	336		360
Deck Width	80			
Deck Height	22			
Coupler Height	17-26			

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.