



SPECIFICATIONS -STEEL GRAVITY TILT STEEL TOPLINE TILT EQUIPMENT 15.4K

	82 x 26	82 x 28	82 x 28	82 x 30
Model #	H-BTE82164-154	H-BTE82166-154	H-BTE82184-154	H-BTE82186-154
CAPACITIES				
GVWR (lbs)	15400			
GAWR (lbs/axle)	7000			
Curb Weight	4040	4140	4070	
Payload	11360	11260	11330	
CHASSIS				
Coupler	Adjustable 4-Bolt Pintle Ring			
Tongue	8" Flange, 13 lb/ft I-Beam			
Tongue Jack	12K, 2-Speed Drop Leg			
Frame	8", 13 lb/ft I-Beam, Tilting Deck - 6" x 4" x 5/16" Reinforced Angle			
Crossmembers	3" x 2" Tube, 16" On-Center			
Axle	(2) 7000 lb. Slipper Spring Brake			
Hubs	Easy Lube			
Exterior Finish	Industrial Grade Polymer Finish			
Tires	ST235/80R16E 10-PLY			
Wheels	16", 8-Lug Steel			
Tie Downs	(4) 3/4" D-Rings, Banjo Tie-Downs, Oversize 5" x 1/4" Thick Stake Pockets			
Wiring	Sealed Wiring Harness			
Exterior Lights	Full LED, DOT Compliant			
Dovetail	Diamond Plate Knife Edge			
Decking	2" Pressure Treated Pine, 4' Stationary, Board Retainers	2" Pressure Treated Pine, 6' Stationary, Board Retainers	2" Pressure Treated Pine, 4' Stationary, Board Retainers	2" Pressure Treated Pine, 6' Stationary, Board Retainers
Exterior Storage	Large Toolbox with Interior Light and Gas Spring, Spare Tire Carrier			
Hydraulic Components	Easy Locking Tilt Bed Latch, Hydraulic Cushion Load Cylinder with Stop Valve			
Coupler Height	17-26			
Deck Height	22			
Height Overall	35			
Width Interior	80			
Width Between Fender	82			
Load Angle	14.5			13
Width Tilting Deck	73.75			
DIMENSIONS				
Overall Length	312	336		360
Deck Width	80			
Deck Height	22			
Coupler Height	17-26			

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -STEEL GRAVITY TILT STEEL TOPLINE TILT EQUIPMENT 17.6K

82 x 26		82 x 28		82 x 28		82 x 30		82 x 30		
Model #	H-BTE82164-176		H-BTE82184-176		H-BTE82166-176		H-BTE82204-176		H-BTE82186-176	
CAPACITIES										
GVWR (lbs)	17600									
GAWR (lbs/axle)	8000									
Curb Weight	4180		4420						4950	
Payload	13420		13180						12650	
CHASSIS										
Coupler	Adjustable Pintle Ring									
Tongue	8" Flange, 13 lb/ft I-Beam									
Tongue Jack	12K, 2-Speed Drop Leg									
Frame	8", 13 lb/ft I-Beam, Tilting Deck - 6" x 4" x 5/16" Reinforced Angle									
Crossmembers	3" x 2" Tube, 16" On-Center									
Axle	(2) 8000 lb. Slipper Spring Brake									
Hubs	Oil Bath									
Exterior Finish	Industrial Grade Polymer Finish									
Tires	215/75R17.5J 18-PLY									
Wheels	17.5", 8-Lug Steel									
Tie Downs	(4) 3/4" D-Rings, Oversize 5" x 1/4" Thick Stake Pockets									
Wiring	Sealed Wiring Harness									
Exterior Lights	Full LED, DOT Compliant									
Bulkhead	HD Bulkhead with Integrated Tie-Down Points									
Dovetail	Diamond Plate Knife Edge									
Decking	2" Pressure Treated Pine, 4' Stationary, Board Retainers			2" Pressure Treated Pine, 6' Stationary, Board Retainers		2" Pressure Treated Pine, 4' Stationary, Board Retainers		2" Pressure Treated Pine, 6' Stationary, Board Retainers		
Exterior Storage	Large Toolbox with Interior Light and Gas Spring, Spare Tire Carrier									
Hydraulic Components	Easy Locking Tilt Bed Latch, Hydraulic Cushion Load Cylinder with Stop Valve									
Coupler Height	17-26							17-26		
Deck Height	22							22		
Height Overall	35							35		
Width Interior	80							80		
Width Between Fender	82							82		
Load Angle	14.5							13		
Width Tilting Deck	73.75							73.75		
DIMENSIONS										
Overall Length	312		336				360			
Deck Width	80							80		
Deck Height	22							22		
Coupler Height	17-26							17-26		

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -STEEL GRAVITY TILT STEEL TOPLINE TILT EQUIPMENT 22K

	82 x 26	82 x 28	82 x 28	82 x 30
Model #	H-BTE82164-220	H-BTE82166-220	H-BTE82184-220	H-BTE82186-220
CAPACITIES				
GVWR (lbs)	22000			
GAWR (lbs/axle)	8000			
CHASSIS				
Coupler	Adjustable 4-Bolt Pintle Ring			
Tongue	8" Flange, 13 lb/ft I-Beam			
Tongue Jack	12K, 2-Speed Drop Leg			
Frame	8", 15 lb/ft I-Beam			
Crossmembers	3" Steel Channel, 16" On-Center			
Axle	(2) 10000 lb. Torsion Brake			
Hubs	Oil Bath			
Exterior Finish	Industrial Grade Polymer Finish			
Tires	ST235/75R17.15J 18-PLY			
Wheels	17.5", 8-Lug Steel			
Tie Downs	(4) 3/4" D-Rings			
Wiring	Sealed Wiring Harness			
Exterior Lights	Full LED, DOT Compliant			
Bulkhead	HD Bulkhead with Integrated Tie-Down Points			
Dovetail	Diamond Plate Knife Edge			
Decking	2" Pressure Treated Pine			
Exterior Storage	Large Toolbox with Interior Light and Gas Spring			
Coupler Height	17-26			
Deck Height	22			
Height Overall	35			
Width Interior	80			
Width Between Fender	82			
Load Angle	14.5			
Width Tilting Deck	73.75			
DIMENSIONS				
Overall Length	312	336		360
Deck Width	80			
Deck Height	22			
Coupler Height	17-26			

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.