



SPECIFICATIONS -DUMP
HDLP HS SCISSOR DUMP 14K

	7 x 14	7 x 14	7 x 16	7 x 16
Model #	ST-HSDU48214-140		ST-HSDU38214-140	ST-HSDU38216-140
CAPACITIES				
GVWR (lbs)	14000			
GAWR (lbs/axle)	7000			
Curb Weight	4560	4355	4740	4985
Payload	9440	9645	9260	9015
CHASSIS				
Coupler	2-5/16" Adjustable			
Tongue		8" x 2" Steel Tube		
Tongue Jack	12K Drop Leg, Set-Back			
Frame	6" x 2" Steel Tube		6" x 2" x 1/4" Steel Tube	
Crossmembers	4" Steel Channel			
Ramp(s)	3" x 80" Steel Ladder Style (Slide-In with Carrier)			
Integrated Step(s)	Side Steps			
Stabilizers	Stabilizer Jack Receivers (Jacks Optional)			
Axle	(2) 7000 lb. Slipper Spring Brake			
Hubs	Easy Lube			
Exterior Finish	Industrial Grade Polymer Finish			
Tires	ST235/80R16E 10-PLY			
Wheels	16", 8-Lug Steel			
Tie Downs	(5) 1/2" D-Rings, Stake Pockets			
Exterior Lights	Full LED, DOT Compliant			
Top Rail	2" x 2" Steel Tube			
Sides	48" Tall Rigid Panels, Board Holders, Integrated Side Body Stiffening System	36" Tall Rigid Panels, Board Holders, Integrated Side Body Stiffening System	48" Tall Rigid Panels, Board Holders, Integrated Side Body Stiffening System	
Gate	NaN			
Decking	10-Gauge Smooth Steel			
Exterior Storage	Drop-In (Recessed) Lockable Battery and Pump Box, Spare Tire Carrier, Underbody Secure Tool Storage			
Hydraulic Components	12 Volt Hydraulic Pump, Power Up, Gravity Down (Scissor Lift Hoist)			
Tarp	18' Mesh Tarp Kit (Installed), Anti-Sail Kit with Integrated Tie-Down, Integrated Tarp Mount and Shroud			
Coupler Height	19-27			
Deck Height	29			
Width Interior	82			
Length Interior Box	168		192	
DIMENSIONS				
Overall Length	222		246	
Deck Width	82			
Deck Height	29			
Coupler Height	19-27			

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -DUMP
HDLP HS SCISSOR DUMP GN 14K

	7 x 14	7 x 14	7 x 16
Model #	ST-HSDU48214-140G	ST-HSDU38214-140G	ST-HSDU48216-140G
CAPACITIES			
GVWR (lbs)	14000		
GAWR (lbs/axle)	7000		
Curb Weight	5410		6080
Payload	8590		7920
CHASSIS			
Coupler	2-5/16" Adjustable Gooseneck		
Tongue Jack	Dual 12K Drop Leg		
Frame	6" x 2" Steel Tube		6" x 2" x 1/4" Steel Tube
Crossmembers	4" Steel Channel		
Ramp(s)	3" x 80" Steel Ladder Style (Slide-In with Carrier)		
Integrated Step(s)	Side Steps		
Stabilizers	Stabilizer Jack Receivers (Jacks Optional)		
Axle	(2) 7000 lb. Slipper Spring Brake		
Hubs	Easy Lube		
Exterior Finish	Industrial Grade Polymer Finish		
Tires	ST235/80R16E 10-PLY		
Wheels	16", 8-Lug Steel		
Tie Downs	(5) 1/2" D-Rings, Stake Pockets		
Exterior Lights	Full LED, DOT Compliant		
Top Rail	2" x 2" Steel Tube		
Sides	Board Holders, Integrated Side Body Stiffening System		
Gate	NaN		
Decking	10-Gauge Smooth Steel		
Exterior Storage	Spare Tire Carrier, Tongue Mounted Lockable Battery and Pump Box, Underbody Secure Tool Storage		
Hydraulic Components	12 Volt Hydraulic Pump, Power Up, Gravity Down (Scissor Lift Hoist)		
Tarp	18' Mesh Tarp Kit (Installed), Anti-Sail Kit with Integrated Tie-Down, Integrated Tarp Mount and Shroud		
Coupler Height	31-39.75		
Deck Height	29		
Width Interior	82		
Length Interior Box	168		192
DIMENSIONS			
Overall Length	276		300
Deck Width	82		
Deck Height	29		
Coupler Height	31-39.75		

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -DUMP HDLP HS TELESCOPIC DUMP 14K

	7 x 14	7 x 14	7 x 16	7 x 16
Model #	ST-HTDU48214-140	ST-HTDU38214-140	ST-HTDU48216-140	ST-HTDU38216-140
CAPACITIES				
GVWR (lbs)	14000			
GAWR (lbs/axle)	7000			
Curb Weight	4360	4080	4665	4420
Payload	9640	9920	9335	9580
CHASSIS				
Coupler	2-5/16" Adjustable			2-5/16" Adjustable
Tongue	6" x 2" Steel Tube			6" x 2" Steel Tube
Tongue Jack	12K Drop Leg, Set-Back			
Frame	6" x 2" Steel Tube			6" x 2" x 1/4" Steel Tube
Crossmembers	4" Steel Channel			4" Steel Channel
Ramp(s)	3" x 80" Steel Ladder Style (Slide-In with Carrier)			3" x 80" Steel Ladder Style (Slide-In with Carrier)
Integrated Step(s)	Side Steps			Side Steps
Stabilizers	Stabilizer Jack Receivers (Jacks Optional)			Stabilizer Jack Receivers (Jacks Optional)
Axle	(2) 7000 lb. Slipper Spring Brake			
Hubs	Easy Lube			
Exterior Finish	Industrial Grade Polymer Finish			Industrial Grade Polymer Finish
Tires	ST235/80R16E 10-PLY			
Wheels	16", 8-Lug Steel			
Tie Downs	(5) 1/2" D-Rings, Stake Pockets			(5) 1/2" D-Rings, Stake Pockets
Exterior Lights	Full LED, DOT Compliant			Full LED, DOT Compliant
Top Rail	2" x 2" Steel Tube			2" x 2" Steel Tube
Sides	Board Holders, Integrated Side Body Stiffening System			Board Holders, Integrated Side Body Stiffening System
Gate	NaN			NaN
Decking	10-Gauge Smooth Steel			10-Gauge Smooth Steel
Exterior Storage	Drop-In (Recessed) Lockable Battery and Pump Box, Spare Tire Carrier, Underbody Secure Tool Storage			Drop-In (Recessed) Lockable Battery and Pump Box, Spare Tire Carrier, Underbody Secure Tool Storage
Hydraulic Components	12 Volt Hydraulic Pump, Power Up, Gravity Down (Telescopic Hoist)			12 Volt Hydraulic Pump, Power Up, Gravity Down (Telescopic Hoist)
Tarp	18' Mesh Tarp Kit (Installed), Anti-Sail Kit with Integrated Tie-Down, Integrated Tarp Mount and Shroud			18' Mesh Tarp Kit (Installed), Anti-Sail Kit with Integrated Tie-Down, Integrated Tarp Mount and Shroud
Coupler Height	19-27			
Deck Height				29
Deck Length			192	
Width Interior				82
Length Interior Box	168			192
DIMENSIONS				
Overall Length	222			246
Deck Length			192	
Deck Width				82
Deck Height				29
Coupler Height			19-27	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -DUMP
HDLP HS TELESCOPIC DUMP GN 14K

7 x 14		7 x 14		7 x 16	
Model #	ST-HTDU38214-140G	ST-HTDU48214-140G		ST-HTDU38216-140G	
CAPACITIES					
GVWR (lbs)	14000				
GAWR (lbs/axle)	7000				
Curb Weight	5210			5270	
Payload	8790			8730	
CHASSIS					
Coupler		2-5/16" Adjustable Gooseneck			
Tongue Jack		Dual 12K Drop Leg			
Frame		6" x 2" Steel Tube		6" x 2" x 1/4" Steel Tube	
Crossmembers		4" Steel Channel			
Ramp(s)		3" x 80" Steel Ladder Style (Slide-In with Carrier)			
Integrated Step(s)		Side Steps			
Stabilizers		Stabilizer Jack Receivers (Jacks Optional)			
Axle		(2) 7000 lb. Slipper Spring Brake			
Hubs		Easy Lube			
Exterior Finish		Industrial Grade Polymer Finish			
Tires		ST235/80R16E 10-PLY			
Wheels		16", 8-Lug Steel			
Tie Downs		(5) 1/2" D-Rings, Stake Pockets			
Exterior Lights		Full LED, DOT Compliant			
Top Rail		2" x 2" Steel Tube			
Sides		Board Holders, Integrated Side Body Stiffening System			
Gate		NaN			
Decking		10-Gauge Smooth Steel			
Exterior Storage		Spare Tire Carrier, Tongue Mounted Lockable Battery and Pump Box, Underbody Secure Tool Storage			
Hydraulic Components		12 Volt Hydraulic Pump, Power Up, Gravity Down (Telescopic Hoist)			
Tarp		18' Mesh Tarp Kit (Installed), Anti-Sail Kit with Integrated Tie-Down, Integrated Tarp Mount and Shroud			
Coupler Height		31-39.75			
Deck Height		29			
Width Interior		82			
Length Interior Box		168		192	
DIMENSIONS					
Overall Length		276		300	
Deck Width		82			
Deck Height		29			
Coupler Height		31-39.75			

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -DUMP
HDLP SCISSOR DUMP 14K

	7 x 12	7 x 14	7 x 16
Model #	ST-HSDU8212-140	ST-HSDU8214-140	ST-HSDU8216-140
CAPACITIES			
GVWR (lbs)	14000		
GAWR (lbs/axle)	7000		
Curb Weight	3955	4155	4495
Payload	10045	9845	9505
CHASSIS			
Coupler	2-5/16" Adjustable		
Tongue	5" x 2" Steel Tube	6" x 2" Steel Tube	
Tongue Jack	12K Drop Leg, Set-Back		
Frame	5" x 2" Steel Tube	6" x 2" Steel Tube	
Crossmembers	4" Steel Channel		
Ramp(s)	3" x 80" Steel Ladder Style (Slide-In with Carrier)		
Integrated Step(s)	Side Steps		
Stabilizers	Stabilizer Jack Receivers (Jacks Optional)		
Axle	(2) 7000 lb. Slipper Spring Brake		
Hubs	Easy Lube		
Exterior Finish	Industrial Grade Polymer Finish		
Tires	ST235/80R16E 10-PLY		
Wheels	16", 8-Lug Steel		
Tie Downs	(5) 1/2" D-Rings, Stake Pockets		
Exterior Lights	Full LED, DOT Compliant		
Top Rail	2" x 2" Steel Tube		
Sides	Board Holders, Integrated Side Body Stiffening System		
Gate	NaN		
Decking	10-Gauge Smooth Steel		
Exterior Storage	Drop-In (Recessed) Lockable Battery and Pump Box, Spare Tire Carrier, Underbody Secure Tool Storage		
Hydraulic Components	12 Volt Hydraulic Pump, Power Up, Gravity Down (Scissor Lift Hoist)		
Tarp	18' Mesh Tarp Kit (Installed), Anti-Sail Kit with Integrated Tie-Down, Integrated Tarp Mount and Shroud		
Coupler Height	19-27		
Deck Height	29		
Width Interior	82		
Length Interior Box	144	168	192
DIMENSIONS			
Overall Length	198	222	246
Deck Width	82		
Deck Height	29		
Coupler Height	19-27		

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -DUMP
HDLP SCISSOR DUMP GN 14K

	7 x 14	7 x 16
Model #	ST-HSDU8214-140G	ST-HSDU8216-140G
CAPACITIES		
GVWR (lbs)	14000	
GAWR (lbs/axle)	7000	
Curb Weight	5005	5345
Payload	8995	8655
CHASSIS		
Coupler	2-5/16" Adjustable Gooseneck	
Tongue Jack	Dual 12K Drop Leg	
Ramp(s)	3" x 80" Steel Ladder Style (Slide-In with Carrier)	
Integrated Step(s)	Side Steps	
Stabilizers	Stabilizer Jack Receivers (Jacks Optional)	
Axle	(2) 7000 lb. Slipper Spring Brake	
Hubs	Easy Lube	
Exterior Finish	Industrial Grade Polymer Finish	
Tires	ST235/80R16E 10-PLY	
Wheels	16", 8-Lug Steel	
Tie Downs	(5) 1/2" D-Rings, Stake Pockets	
Exterior Lights	Full LED, DOT Compliant	
Top Rail	2" x 2" Steel Tube	
Sides	Board Holders, Integrated Side Body Stiffening System	
Gate	NaN	
Decking	10-Gauge Smooth Steel	
Exterior Storage	Spare Tire Carrier, Tongue Mounted Lockable Battery and Pump Box, Underbody Secure Tool Storage	
Tarp	18' Mesh Tarp Kit (Installed), Anti-Sail Kit with Integrated Tie-Down, Integrated Tarp Mount and Shroud	
Coupler Height	31-39.75	
Deck Height	29	
Width Interior	82	
Length Interior Box	168	192
DIMENSIONS		
Overall Length	276	300
Deck Width	82	
Deck Height	29	
Coupler Height	31-39.75	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -DUMP
HDLP TELESCOPIC DUMP 14K

	7 x 12	7 x 14	7 x 16
Model #	ST-HTDU8212-140	ST-HTDU8214-140	ST-HTDU8216-140
CAPACITIES			
GVWR (lbs)		14000	
GAWR (lbs/axle)		7000	
Curb Weight	3795	3955	4175
Payload	10205	10045	9825
CHASSIS			
Coupler		2-5/16" Adjustable	
Tongue		6" x 2" Steel Tube	
Tongue Jack		12K Drop Leg, Set-Back	
Frame		6" x 2" Steel Tube	
Crossmembers		4" Steel Channel	
Ramp(s)		3" x 80" Steel Ladder Style (Slide-In with Carrier)	
Integrated Step(s)		Side Steps	
Stabilizers		Stabilizer Jack Receivers (Jacks Optional)	
Axle		(2) 7000 lb. Slipper Spring Brake	
Hubs		Easy Lube	
Exterior Finish		Industrial Grade Polymer Finish	
Tires		ST235/80R16E 10-PLY	
Wheels		16", 8-Lug Steel	
Tie Downs		(5) 1/2" D-Rings, Stake Pockets	
Exterior Lights		Full LED, DOT Compliant	
Top Rail		2" x 2" Steel Tube	
Sides		Board Holders, Integrated Side Body Stiffening System	
Gate		NaN	
Decking		10-Gauge Smooth Steel	
Exterior Storage		Drop-In (Recessed) Lockable Battery and Pump Box, Spare Tire Carrier, Underbody Secure Tool Storage	
Hydraulic Components		12 Volt Hydraulic Pump, Power Up, Gravity Down (Telescopic Hoist)	
Tarp		18' Mesh Tarp Kit (Installed), Anti-Sail Kit with Integrated Tie-Down, Integrated Tarp Mount and Shroud	
Coupler Height		19-27	
Deck Height		29	
Width Interior		82	
Length Interior Box	144	168	192
DIMENSIONS			
Overall Length	198	222	246
Deck Width		82	
Deck Height		29	
Coupler Height		19-27	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -DUMP
HDLP TELESCOPIC DUMP GN 14K

	7 x 14	7 x 16
Model #	ST-HTDU8214-140G	ST-HTDU8216-140G
CAPACITIES		
GVWR (lbs)	14000	
GAWR (lbs/axle)	7000	
Curb Weight	4805	5025
Payload	9195	8975
CHASSIS		
Coupler	2-5/16" Adjustable Gooseneck	
Tongue Jack	Dual 12K Drop Leg	
Ramp(s)	3" x 80" Steel Ladder Style (Slide-In with Carrier)	
Integrated Step(s)	Side Steps	
Stabilizers	Stabilizer Jack Receivers (Jacks Optional)	
Axle	(2) 7000 lb. Slipper Spring Brake	
Hubs	Easy Lube	
Exterior Finish	Industrial Grade Polymer Finish	
Tires	ST235/80R16E 10-PLY	
Wheels	16", 8-Lug Steel	
Tie Downs	(5) 1/2" D-Rings, Stake Pockets	
Exterior Lights	Full LED, DOT Compliant	
Top Rail	2" x 2" Steel Tube	
Sides	Board Holders, Integrated Side Body Stiffening System	
Gate	NaN	
Decking	10-Gauge Smooth Steel	
Exterior Storage	Spare Tire Carrier, Tongue Mounted Lockable Battery and Pump Box, Underbody Secure Tool Storage	
Tarp	18' Mesh Tarp Kit (Installed), Anti-Sail Kit with Integrated Tie-Down, Integrated Tarp Mount and Shroud	
Coupler Height	31-39.75	
Deck Height	29	
Width Interior	82	
Length Interior Box	168	192
DIMENSIONS		
Overall Length	276	300
Deck Width	82	
Deck Height	29	
Coupler Height	31-39.75	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -DUMP
HDLP HS SCISSOR DUMP 16K

	7 x 14	7 x 14	7 x 16	7 x 16
Model #	ST-HSDU38214-160	ST-HSDU48214-160	ST-HSDU48216-160	ST-HSDU38216-160
CAPACITIES				
GVWR (lbs)	16000			
GAWR (lbs/axle)	8000			
Curb Weight	4700		5225	
Payload	11300		10775	
CHASSIS				
Coupler	Adjustable 4-Bolt Pintle Ring			
Tongue	8" x 2" Steel Tube			
Tongue Jack	12K Drop Leg, Set-Back			
Frame	6" x 2" x 1/4" Steel Tube			
Crossmembers	4" Steel Channel			
Ramp(s)	4" x 80" Steel Ladder Style (Slide-In with Carrier)			
Integrated Step(s)	Side Steps			
Stabilizers	Stabilizer Jack Receivers (Jacks Optional)			
Axle	(2) 8000 lb. Slipper Spring Brake			
Hubs	Oil Bath			
Exterior Finish	Industrial Grade Polymer Finish			
Tires	215/75R17.5J 18-PLY			
Wheels	17.5", 8-Lug Steel			
Tie Downs	(5) 1/2" D-Rings, Stake Pockets			
Exterior Lights	Full LED, DOT Compliant			
Top Rail	2" x 2" Steel Tube			
Sides	Board Holders, Integrated Side Body Stiffening System			
Gate	NaN			
Decking	10-Gauge Smooth Steel			
Exterior Storage	Drop-In (Recessed) Lockable Battery and Pump Box, Spare Tire Carrier, Underbody Secure Tool Storage			
Hydraulic Components	12 Volt Hydraulic Pump, Power Up, Gravity Down (Scissor Lift Hoist)			
Tarp	18' Mesh Tarp Kit (Installed), Anti-Sail Kit with Integrated Tie-Down, Integrated Tarp Mount and Shroud			
Coupler Height	19-27			
Deck Height	29			
Width Interior	82			
Length Interior Box	168		192	
DIMENSIONS				
Overall Length	222		246	
Deck Width	82			
Deck Height	29			
Coupler Height	19-27			

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -DUMP
HDLP HS SCISSOR DUMP GN 16K

7 x 14		7 x 14
Model #	ST-HSDU38214-160G	ST-HSDU48214-160G
CAPACITIES		
GVWR (lbs)	16000	
GAWR (lbs/axle)	8000	
Curb Weight	5550	
Payload	10450	
CHASSIS		
Coupler	2-5/16" Adjustable Gooseneck	
Tongue Jack	Dual 12K Drop Leg	
Frame	6" x 2" x 1/4" Steel Tube	
Crossmembers	4" Steel Channel	
Ramp(s)	4" x 80" Steel Ladder Style (Slide-In with Carrier)	
Integrated Step(s)	Side Steps	
Stabilizers	Stabilizer Jack Receivers (Jacks Optional)	
Axle	(2) 8000 lb. Slipper Spring Brake	
Hubs	Oil Bath	
Exterior Finish	Industrial Grade Polymer Finish	
Tires	215/75R17.5J 18-PLY	
Wheels	17.5", 8-Lug Steel	
Tie Downs	(5) 1/2" D-Rings, Stake Pockets	
Exterior Lights	Full LED, DOT Compliant	
Top Rail	2" x 2" Steel Tube	
Sides	Board Holders, Integrated Side Body Stiffening System	
Gate	NaN	
Decking	10-Gauge Smooth Steel	
Exterior Storage	Spare Tire Carrier, Tongue Mounted Lockable Battery and Pump Box, Underbody Secure Tool Storage	
Hydraulic Components	12 Volt Hydraulic Pump, Power Up, Gravity Down (Scissor Lift Hoist)	
Tarp	18' Mesh Tarp Kit (Installed), Anti-Sail Kit with Integrated Tie-Down, Integrated Tarp Mount and Shroud	
Coupler Height	31-39.75	
Deck Height	29	
Width Interior	82	
Length Interior Box	168	192
DIMENSIONS		
Overall Length	276	300
Deck Width	82	
Deck Height	29	
Coupler Height	31-39.75	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -DUMP
HDLP HS TELESCOPIC DUMP 16K

	7 x 14	7 x 14	7 x 16	7 x 16
Model #	ST-HTDU38214-160	ST-HTDU48214-160	ST-HTDU38216-160	ST-HTDU48216-160
CAPACITIES				
GVWR (lbs)	16000			
GAWR (lbs/axle)	8000			
Curb Weight	5060	4600	4905	
Payload	10940	11400	11095	
CHASSIS				
Coupler	Adjustable 4-Bolt Pintle Ring			
Tongue	8" x 2" Steel Tube			
Tongue Jack	12K Drop Leg, Set-Back			
Frame	6" x 2" Steel Tube		6" x 2" x 1/4" Steel Tube	
Crossmembers	4" Steel Channel			
Ramp(s)	4" x 80" Steel Ladder Style (Slide-In with Carrier)			
Integrated Step(s)	Side Steps			
Stabilizers	Stabilizer Jack Receivers (Jacks Optional)			
Axle	(2) 8000 lb. Slipper Spring Brake			
Hubs	Oil Bath			
Exterior Finish	Industrial Grade Polymer Finish			
Tires	215/75R17.5J 18-PLY			
Wheels	17.5", 8-Lug Steel			
Tie Downs	(5) 1/2" D-Rings, Stake Pockets			
Exterior Lights	Full LED, DOT Compliant			
Top Rail	2" x 2" Steel Tube			
Sides	Board Holders, Integrated Side Body Stiffening System			
Gate	NaN			
Decking	10-Gauge Smooth Steel			
Exterior Storage	Drop-In (Recessed) Lockable Battery and Pump Box, Spare Tire Carrier, Underbody Secure Tool Storage			
Hydraulic Components	12 Volt Hydraulic Pump, Power Up, Gravity Down (Telescopic Hoist)			
Tarp	18' Mesh Tarp Kit (Installed), Anti-Sail Kit with Integrated Tie-Down, Integrated Tarp Mount and Shroud			
Coupler Height	19-27			
Deck Height	29			
Width Interior	82			
Length Interior Box	168		192	
DIMENSIONS				
Overall Length	222		246	
Deck Width	82			
Deck Height	29			
Coupler Height	19-27			

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -DUMP
HDLP HS TELESCOPIC DUMP GN 16K

	7 x 14	7 x 14	7 x 16	7 x 16
Model #	ST-HTDU38214-160G	ST-HTDU48214-160G	ST-HTDU38216-160G	ST-HTDU48216-160G
CAPACITIES				
GVWR (lbs)	16000			
GAWR (lbs/axle)	8000			
Curb Weight	5940		5755	
Payload	10060		10245	
CHASSIS				
Coupler	2-5/16" Adjustable Gooseneck			
Tongue Jack	Dual 12K Drop Leg			
Frame	6" x 2" x 1/4" Steel Tube			
Crossmembers	4" Steel Channel			
Ramp(s)	4" x 80" Steel Ladder Style (Slide-In with Carrier)			
Integrated Step(s)	Side Steps			
Stabilizers	Stabilizer Jack Receivers (Jacks Optional)			
Axle	(2) 8000 lb. Slipper Spring Brake			
Hubs	Oil Bath			
Exterior Finish	Industrial Grade Polymer Finish			
Tires	215/75R17.5J 18-PLY			
Wheels	17.5", 8-Lug Steel			
Tie Downs	(5) 1/2" D-Rings, Stake Pockets			
Exterior Lights	Full LED, DOT Compliant			
Top Rail	2" x 2" Steel Tube			
Sides	Board Holders, Integrated Side Body Stiffening System			
Gate	NaN			
Decking	10-Gauge Smooth Steel			
Exterior Storage	Spare Tire Carrier, Tongue Mounted Lockable Battery and Pump Box, Underbody Secure Tool Storage			
Hydraulic Components	12 Volt Hydraulic Pump, Power Up, Gravity Down (Telescopic Hoist)			
Tarp	18' Mesh Tarp Kit (Installed), Anti-Sail Kit with Integrated Tie-Down, Integrated Tarp Mount and Shroud			
Coupler Height	31-39.75			
Deck Height	29			
Width Interior	82			
Length Interior Box	168		192	
DIMENSIONS				
Overall Length	276		300	
Deck Width	82			
Deck Height	29			
Coupler Height	31-39.75			

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -DUMP
HDLP SCISSOR DUMP 16K

	7 x 14	7 x 16
Model #	ST-HSDU8214-160	ST-HSDU8216-160
CAPACITIES		
GVWR (lbs)	16000	
GAWR (lbs/axle)	8000	
Curb Weight	4395	4735
Payload	11605	11265
CHASSIS		
Coupler	Adjustable 4-Bolt Pintle Ring	
Tongue	8" x 2" Steel Tube	
Tongue Jack	12K Drop Leg, Set-Back	
Frame	5" x 2" Steel Tube	6" x 2" Steel Tube
Crossmembers	4" Steel Channel	
Ramp(s)	3" x 80" Steel Ladder Style (Slide-In with Carrier)	
Integrated Step(s)	Side Steps	
Stabilizers	Stabilizer Jack Receivers (Jacks Optional)	
Axle	(2) 8000 lb. Slipper Spring Brake	
Hubs	Oil Bath	
Exterior Finish	Industrial Grade Polymer Finish	
Tires	215/75R17.5J 18-PLY	
Wheels	17.5", 8-Lug Steel	
Tie Downs	(5) 1/2" D-Rings, Stake Pockets	
Exterior Lights	Full LED, DOT Compliant	
Top Rail	2" x 2" Steel Tube	
Sides	Board Holders, Integrated Side Body Stiffening System	
Gate	NaN	
Decking	10-Gauge Smooth Steel	
Exterior Storage	Drop-In (Recessed) Lockable Battery and Pump Box, Spare Tire Carrier, Underbody Secure Tool Storage	
Hydraulic Components	12 Volt Hydraulic Pump, Power Up, Gravity Down (Scissor Lift Hoist)	
Tarp	18' Mesh Tarp Kit (Installed), Anti-Sail Kit with Integrated Tie-Down, Integrated Tarp Mount and Shroud	
Coupler Height	19-27	
Deck Height	29	
Width Interior	82	
Length Interior Box	168	192
DIMENSIONS		
Overall Length	222	246
Deck Width	82	
Deck Height	29	
Coupler Height	19-27	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -DUMP
HDLP SCISSOR DUMP GN 16K

	7 x 14	7 x 16
Model #	ST-HSDU8214-160G	ST-HSDU8216-160G
CAPACITIES		
GVWR (lbs)	16000	
GAWR (lbs/axle)	8000	
Curb Weight	5245	5585
Payload	10755	10415
CHASSIS		
Coupler	2-5/16" Adjustable Gooseneck	
Tongue Jack	Dual 12K Drop Leg	
Ramp(s)	3" x 80" Steel Ladder Style (Slide-In with Carrier)	
Integrated Step(s)	Side Steps	
Stabilizers	Stabilizer Jack Receivers (Jacks Optional)	
Axle	(2) 8000 lb. Slipper Spring Brake	
Hubs	Oil Bath	
Exterior Finish	Industrial Grade Polymer Finish	
Tires	215/75R17.5J 18-PLY	
Wheels	17.5", 8-Lug Steel	
Tie Downs	(5) 1/2" D-Rings, Stake Pockets	
Exterior Lights	Full LED, DOT Compliant	
Top Rail	2" x 2" Steel Tube	
Sides	Board Holders, Integrated Side Body Stiffening System	
Gate	NaN	
Decking	10-Gauge Smooth Steel	
Exterior Storage	Spare Tire Carrier, Tongue Mounted Lockable Battery and Pump Box, Underbody Secure Tool Storage	
Tarp	18' Mesh Tarp Kit (Installed), Anti-Sail Kit with Integrated Tie-Down, Integrated Tarp Mount and Shroud	
Coupler Height	31-39.75	
Deck Height	29	
Width Interior	82	
Length Interior Box	168	192
DIMENSIONS		
Overall Length	276	300
Deck Width	82	
Deck Height	29	
Coupler Height	31-39.75	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -DUMP
HDLP TELESCOPIC DUMP 16K

	7 x 14	7 x 16
Model #	ST-HTDU8214-160	ST-HTDU8216-160
CAPACITIES		
GVWR (lbs)	16000	
GAWR (lbs/axle)	8000	
Curb Weight	4650	4415
Payload	11350	11585
CHASSIS		
Coupler	Adjustable 4-Bolt Pintle Ring	
Tongue	8" x 2" Steel Tube	
Tongue Jack	12K Drop Leg, Set-Back	
Frame	6" x 2" Steel Tube	
Crossmembers	4" Steel Channel	
Ramp(s)	3" x 80" Steel Ladder Style (Slide-In with Carrier)	
Integrated Step(s)	Side Steps	
Stabilizers	Stabilizer Jack Receivers (Jacks Optional)	
Axle	(2) 8000 lb. Slipper Spring Brake	
Hubs	Oil Bath	
Exterior Finish	Industrial Grade Polymer Finish	
Tires	215/75R17.5J 18-PLY	
Wheels	17.5", 8-Lug Steel	
Tie Downs	(5) 1/2" D-Rings, Stake Pockets	
Exterior Lights	Full LED, DOT Compliant	
Top Rail	2" x 2" Steel Tube	
Sides	Board Holders, Integrated Side Body Stiffening System	
Gate	NaN	
Decking	10-Gauge Smooth Steel	
Exterior Storage	Drop-In (Recessed) Lockable Battery and Pump Box, Spare Tire Carrier, Underbody Secure Tool Storage	
Hydraulic Components	12 Volt Hydraulic Pump, Power Up, Gravity Down (Telescopic Hoist)	
Tarp	18' Mesh Tarp Kit (Installed), Anti-Sail Kit with Integrated Tie-Down, Integrated Tarp Mount and Shroud	
Coupler Height	19-27	
Deck Height	29	
Width Interior	82	
Length Interior Box	168	192
DIMENSIONS		
Overall Length	222	246
Deck Width	82	
Deck Height	29	
Coupler Height	19-27	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -DUMP
HDLP TELESCOPIC DUMP GN 16K

	7 x 14	7 x 16
Model #	ST-HTDU8214-160G	ST-HTDU8216-160G
CAPACITIES		
GVWR (lbs)	16000	
GAWR (lbs/axle)	8000	
Curb Weight	5045	5265
Payload	10955	10735
CHASSIS		
Coupler	2-5/16" Adjustable Gooseneck	
Tongue Jack	Dual 12K Drop Leg	
Ramp(s)	3" x 80" Steel Ladder Style (Slide-In with Carrier)	
Integrated Step(s)	Side Steps	
Stabilizers	Stabilizer Jack Receivers (Jacks Optional)	
Axle	(2) 8000 lb. Slipper Spring Brake	
Hubs	Oil Bath	
Exterior Finish	Industrial Grade Polymer Finish	
Tires	215/75R17.5J 18-PLY	
Wheels	17.5", 8-Lug Steel	
Tie Downs	(5) 1/2" D-Rings, Stake Pockets	
Exterior Lights	Full LED, DOT Compliant	
Top Rail	2" x 2" Steel Tube	
Sides	Board Holders, Integrated Side Body Stiffening System	
Gate	NaN	
Decking	10-Gauge Smooth Steel	
Exterior Storage	Spare Tire Carrier, Tongue Mounted Lockable Battery and Pump Box, Underbody Secure Tool Storage	
Tarp	18' Mesh Tarp Kit (Installed), Anti-Sail Kit with Integrated Tie-Down, Integrated Tarp Mount and Shroud	
Coupler Height	31-39.75	
Deck Height	29	
Width Interior	82	
Length Interior Box	168	192
DIMENSIONS		
Overall Length	276	300
Deck Width	82	
Deck Height	29	
Coupler Height	31-39.75	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -DUMP
HDLP SCISSOR DUMP 12K

7 x 12	
Model #	ST-HSDU8212-120
CAPACITIES	
GVWR (lbs)	12000
GAWR (lbs/axle)	6000
Curb Weight	3735
Payload	8265
CHASSIS	
Coupler	2-5/16" Adjustable
Tongue	5" x 2" Steel Tube
Tongue Jack	7K Drop Leg, Set-Back
Frame	5" x 2" Steel Tube
Crossmembers	4" Steel Channel
Ramp(s)	3" x 80" Steel Ladder Style (Slide-In with Carrier)
Integrated Step(s)	Side Steps
Stabilizers	Stabilizer Jack Receivers (Jacks Optional)
Axle	(2) 6000 lb. Slipper Spring Brake
Hubs	Easy Lube
Exterior Finish	Industrial Grade Polymer Finish
Tires	ST235/80R16E 10-PLY
Wheels	16", 8-Lug Steel
Tie Downs	(5) 1/2" D-Rings, Stake Pockets
Exterior Lights	Full LED, DOT Compliant
Top Rail	2" x 2" Steel Tube
Sides	Board Holders, Integrated Side Body Stiffening System
Gate	NaN
Decking	10-Gauge Smooth Steel
Exterior Storage	Drop-In (Recessed) Lockable Battery and Pump Box, Spare Tire Carrier, Underbody Secure Tool Storage
Hydraulic Components	12 Volt Hydraulic Pump, Power Up, Gravity Down (Scissor Lift Hoist)
Tarp	18' Mesh Tarp Kit (Installed), Anti-Sail Kit with Integrated Tie-Down, Integrated Tarp Mount and Shroud
Coupler Height	19-27
Deck Height	29
Width Interior	82
Length Interior Box	144
DIMENSIONS	
Overall Length	198
Deck Width	82
Deck Height	29
Coupler Height	19-27

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -DUMP
HDLP TELESCOPIC DUMP 12K

7 x 12	
Model #	ST-HTDU8212-120
CAPACITIES	
GVWR (lbs)	12000
GAWR (lbs/axle)	6000
Curb Weight	3575
Payload	8425
CHASSIS	
Coupler	2-5/16" Adjustable
Tongue	6" x 2" Steel Tube
Tongue Jack	7K Drop Leg, Set-Back
Frame	6" x 2" Steel Tube
Crossmembers	4" Steel Channel
Ramp(s)	3" x 80" Steel Ladder Style (Slide-In with Carrier)
Integrated Step(s)	Side Steps
Stabilizers	Stabilizer Jack Receivers (Jacks Optional)
Axle	(2) 6000 lb. Slipper Spring Brake
Hubs	Easy Lube
Exterior Finish	Industrial Grade Polymer Finish
Wheels	16", 8-Lug Steel
Tie Downs	(5) 1/2" D-Rings, Stake Pockets
Exterior Lights	Full LED, DOT Compliant
Top Rail	2" x 2" Steel Tube
Sides	Board Holders, Integrated Side Body Stiffening System
Gate	NaN
Decking	10-Gauge Smooth Steel
Exterior Storage	Drop-In (Recessed) Lockable Battery and Pump Box, Spare Tire Carrier, Underbody Secure Tool Storage
Hydraulic Components	12 Volt Hydraulic Pump, Power Up, Gravity Down (Telescopic Hoist)
Tarp	18' Mesh Tarp Kit (Installed), Anti-Sail Kit with Integrated Tie-Down, Integrated Tarp Mount and Shroud
Coupler Height	19-27
Deck Height	29
Width Interior	82
Length Interior Box	144
DIMENSIONS	
Overall Length	198
Deck Width	82
Deck Height	29
Coupler Height	19-27

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.